

SMP-PRO4 Zone-Type Digital Signage Player



Zone-type fanless digital signage player with AV-in supporting portrait mode, real-time video, playback of image slide show, ticker text, video, and clock in maximum six zones.

Main Features

Multimedia Presentation

- Zone-type presentation supporting one background design, one multimedia (stored video/streaming video/image/music) area, two image slide show areas, one ticker area, and one clock & date area
- Support easy settings of ticker by entering texts directly in the web-based user interface, or feed texts from a text file, URL, or RSS feed.
- Play real-time video by directly connecting to a TV tuner, DVD player, USB Camera (UVC compatible), etc.
- Support various resolutions for standard (4:3) and wide screens (16:9) in both portrait and landscape displays.



Easy Template Creation

- Equipped with pre-designed skins and stylish clocks for users to create attractive presentations easily.
- Packed with a handy tool, Skin Editor, with an intuitive drag-and-drop user interface. Users can define the size and location of each zone freely and create skin and clock files.

Local and Central Scheduling

- Edit schedule directly on individual SMP player or centrally control multiple players in groups by CAYIN CMS server.
- Edit playlist and playback multimedia contents based on a pre-set schedule.
- Turn on/off display and adjust volume manually or by a pre-set schedule.

Powerful Remote Management


- Manage each player remotely by a web-based user interface via wired/wireless network.
- Complete step-by-step configuration via Wizard Mode.
- Turn on/off screens, or control other devices by RS-232.
- Recover system remotely for easy maintenance.
- Create log files recording the system
 status for management and analysis purposes. Users can purchase
 SuperReporter 2 to generate advanced reports.
- Manage the player as a standalone system or incorporate it with CAYIN CMS server as a server-client structure.
- Trigger emergency mode via CAYIN CMS server or SuperMonitor 3
- Hardware watchdog timer, CPU temperature.

Content Update

Update multimedia contents by USB flash drive (offline), FTP, Network Neighborhood, or by CAYIN CMS server with automatic centralized content update according to the pre-set schedule through LAN or the Internet.



I/O Interface



Specifications

System Specifications		
Operating System	Embedded Linux	
Display Zone	1 JPEG Theme Background	1 Multimedia Area (Video/Streaming/Image/Audio Area)
	• 1 Ticker (Scrolling Text)	• 2 Image Slide Show Areas (JPG or GIF)
	1 Date & Clock Area	
Media Player	• Video File Format: MPEG (MPG, VOB), AVI, WMV, WMA, MP3, MP4	• Video Codec: MPEG-1/2, MPEG-4 ISO, WMV 7/8/9, RAW DV, H.264
	• Video Streaming Format: RTB (MPEG4-TS, MPEG2-TS), RTP, MMS, HTTP	• Audio Codec: MP-3, WMA 7/8
	• Support up to 720p (1280x720)	• Support video bit-rate up to 10 Mbps (codec dependent, landscape)
Image Slide Show	JPEG or GIF Files	
Ticker (Scrolling Text)	t) • Enter text in Web Manager	Read text files in Hard-disk Drive
	Get text file or RSS feed from remote web server	
Scheduling	• Run Once (by event) or emergency event with CAYIN CMS server	• Weekly
Display	• Screen Resolution: 640x480, 800x600, 1024x768, 1152x864, 1280x1024, 1280x720 (720p), 1280x768, 1600x900, 1360x768, 1366x768	
	Portrait Mode: Support 90 and 270 degree display rotation	
	Clone mode: Support to show one content on two screens via VGA and DVI connectors	

Hardware Specifications • 268 (W) x 174 (D) x 47 (H) mm Dimension Material Aluminum + Steel (Fanless) Weight • 2.2 Kg (with hard drive) • 10/100/1000 Mbps Ethernet Network • 802.11 b/g WIFI controller (optional) Internal Storage • 160G Byte, 2.5" SATA HD Video • VGA D-Sub, DVI-D (no HDCP support) • RCA (Stereo) Audio Video in S-Video Audio in · RCA (Stereo) Power • 100~240V AC (with external adaptor) Others • 2 x RS-232 (COM), 4 x USB Certificate • CE, FCC, LVD, RoHS, CB, CCC

* Specifications subject to change without notice.

CAYIN Technology Co., Ltd. 8F, No. 577, Linsen N. Rd., Taipei City 104, Taiwan TEL: +886-2-25951005 FAX: +886-2-25951050 sales@cayintech.com www.cayintech.com